

CAVABRASIVO 10



Suction and delivery hose suitable for dry abrasive products

DESCRIPTION

Tube

NR/SBR, black, conductive

Reinforcement

synthetic plies, steel wire helices, on request a/s wires to discharge static electricity

Cover

smooth, black, conductive, abrasion, ageing and ozone resistant, cloth finish

TECHNICAL CHARACTERISTICS

Temperature range: -40°C / +70°C (-40°F / +158°F)

Norms : ISO 1307 for dimensional tolerances

Inside diameter		Outside diameter		Lenght		Vacuum		Working pressure		Burst pressure		Appr. weight		Bending radius	
[mm]	[in]	[mm]	[in]	[mt]	[ft]	[bar]	[psi]	[bar]	[psi]	[bar]	[psi]	[kg/mt]	[lbs/ft]	[mm]	[in]
51	2,00	64	2,51	40	130	0,9	13	10	150	30	450	1,61	1,08	200	7,87
75	2,92	90	3,54	40	130	0,9	13	10	150	30	450	2,78	1,86	300	11,81
76	3,00	91	3,60	40	130	0,9	13	10	150	30	450	2,80	1,88	300	11,81
90	3,54	106	4,17	40	130	0,9	13	10	150	30	450	3,56	2,39	360	14,17
102	4,00	120	4,72	40	130	0,9	13	10	150	30	450	4,44	2,98	430	16,92
127	5,00	146	5,74	40	130	0,8	11,5	10	150	30	450	5,94	4,00	620	24,40
152	6,00	178	7,00	40	130	0,8	11,5	10	150	30	450	10,18	6,84	780	30,70
200	7,87	230	9,05	40	130	0,8	11,5	10	150	30	450	14,94	10,03	1050	41,33
203	8,00	233	9,17	20	65	0,8	11,5	10	150	30	450	15,15	10,18	1050	41,33

Other diameters, wall thickness and pressure only on specific request.
Data refer to ambient temperature (20 °C)