


Knaggen mit Innengewinde-Stutzen, drehbar

Heads with female thread-tail, swivel

Dichtung: Nitril-Kautschuk schwarz / weiß
Viton Dichtung bei V4A

Seal: Nitrile rubber black / white
Fluoro rubber - Stainless steel

Gewinde - thread: **DIN ISO 228**



Aluminium light alloy	Messing copper alloy	Edelstahl stainless steel
--------------------------	-------------------------	------------------------------

Storz Size	KA (mm) Lug	Innengewinde (w) Female thread	Weight (kg)	Ident-No.	Euro
25-D	31	G ¾ "	0,36	23-031075-30	
		G 1 "	0,38	23-031100-30	
52-C	66	G 1¼ "	0,47	23-066125-10	
		G 1½ "	0,46	23-066150-10	
		G 1½ "	1,13	23-066150-43	
		G 2 "	0,36	23-066200-10	
		G 2 "	1,52	23-066200-30	
		G 2 "	0,98	23-066200-43	
		G 2 "	0,59	23-081200-10	
65	81	G 2½ "	0,78	23-081250-10	
		G 3 "	0,81	23-081300-10	
		G 2 "	0,74	23-089200-10	
75-B	89	G 2 "	2,23	23-089200-43	
		G 2½ "	0,57	23-089250-10	
		G 2½ "	1,48	23-089250-43	
		G 3 "	0,76	23-089300-10	
		G 3 "	2,54	23-089300-43	
		G 3 "	0,70	23-105300-10	
90	105	G 3 "	0,70	23-105300-10	
100	115	G 4 "	1,27	23-115400-10	
110-A	133	G 3 "	1,79	23-133300-10	
		G 4 "	1,46	23-133400-10	
		G 4 "	4,28	23-133400-43	
125	148	G 4 "	1,59	23-148400-10	
		G 5 "	2,27	23-148500-10	
150	160	G 4 "	2,76	23-160400-10	
		G 5 "	2,87	23-160500-10	
		G 6 "	3,25	23-160600-10	

Auf Wunsch: obige Teile mit Verriegelung (siehe Seite 7)

On demand: above parts with locking device (see page 7)